

Product Sheet 2SLA260L

TECHNICAL DATA		LAYOUT
Voltage	2.00 V	
Performance	260Ah C10 1.80V/cell 20°C	
Float Voltage	2.27V/cell at 20°C	
Connection torque	10 - 12 Nm	
Max Charge Current	65.00 A	
Weight (Typical)	16,40 kg	
Internal Resistance	0.63 mΩ	
Short Circuit Current	3400.00 A	

ELECTRICAL PERFORMANCES - Including Fiamm connection voltage drop

Constant Current Discharge Table [A] at 20°C

V / cell	5 min	10 min	15 min	30 min	45 min	1 h	2 h	3 h	4 h	5 h	6 h	8 h	10 h
1,60	818	624	511	319	231	185	106	75,4	58,4	48,2	40,8	32,0	26,6
1,65	803	615	505	316	229	183	105	74,7	58,1	47,9	40,7	31,9	26,5
1,67	796	611	502	314	228	182	104	74,4	57,9	47,8	40,6	31,9	26,5
1,70	789	607	499	313	227	181	104	74,0	57,8	47,7	40,6	31,9	26,4
1,75	745	589	488	307	222	177	101	72,7	57,1	47,3	40,3	31,7	26,3
1,80	680	554	465	294	214	169	96,2	70,0	55,9	46,4	39,8	31,5	26,0
1,85	532	453	383	251	189	154	90,7	66,0	51,5	43,4	38,2	30,2	25,2
1,90	451	398	342	228	175	143	84,1	61,0	48,2	40,5	35,3	28,0	23,4

Constant Power Discharge Table [W/cell] at 25°C

V / cell	5 min	10 min	15 min	30 min	45 min	1 h	2 h	3 h	4 h	5 h	6 h	8 h	10 h
1,60	1476	1152	952	608	444	357	208	146	114	93,9	79,9	62,8	52,3
1,65	1475	1150	952	608	444	357	207	145	113	93,9	80,0	62,9	52,3
1,67	1471	1148	952	608	444	357	207	145	114	94,0	80,0	62,9	52,3
1,70	1467	1146	952	608	444	357	206	145	114	94,1	80,1	63,0	52,3
1,75	1424	1142	951	606	442	353	203	144	113	93,8	80,1	63,1	52,3
1,80	1326	1094	925	589	431	342	196	140	112	93,1	79,8	63,2	52,3
1,85	1059	910	774	510	387	315	187	134	104	88,0	77,4	61,3	51,2
1,90	906	808	696	467	360	295	174	124	98,4	82,6	72,0	57,2	47,9